

01B5 electric lifting and lowering

Mod. **01B5** is a counterbalanced workshop crane (built-in ballast weights) with a **360°** pivoting arm, suitable for handling industrial equipment up to **500 kg** in line with Safety international standards.

The crane is fitted with a pendant control station for electric lifting and lowering of the jib, and an emergency button.

It comes with a traction battery and battery charger. Easy to move, thanks to its high capacity pivoting wheels fitted with foot brakes.

It has a compact structure (frontal size **995 mm**) so it can be easily maneuvered into position on congested sites and narrow lanes. Jib is extendible in 4 positions.

Optional jib extension is available to increase the crane maximum reach up to **1360 mm** (at 160 kg capacity).

Cylinder		
Stroke	Ø	Ø Stem
[mm]	[mm]	[mm]
470	60	30

Technical data 01B5		
Weight	[kg]	651
Max capacity	[kg]	500
Max pressure	[BAR]	160
Power	[W]	300
Tank capacity	[L]	2

Outreach with standard jib		
Position	Length	Capacity
	[mm]	[kg]
1	455	500
2	590	420
3	725	370
4	860	320

Outreach with extension jib (optional)		
Position	Length	Capacity
	[mm]	[kg]
1	955	220
2	1090	200
3	1225	180
4	1360	160

Battery (1x Traction type)	[V]	12
	[A]	80
Battery charger	[V]	220
	[A]	12

High frequency battery charger, switching technology with noise filter complies with EMC regulations.

